

IES ROAD REPORT
PHOTOMETRIC FILENAME : 4000118LP.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] ERL2178
[TESTLAB] ERL
[ISSUEDATE] 7/3/2008
[TESTDATE] 3/28/1977
[MANUFAC] ABS LIGHTING
[LUMCAT] 4000-1-18LPS
[LUMINAIRE] 4000 SERIES, TYPE 1 FULL CUTOFF, DIE-FORMED AND
[MORE] SEAM WELDED HOUSING, CURVED SPECULAR ALZAK
[MORE] REFLECTOR, 1/8" CLEAR LEXAN LENS
[MORE] CAN BE TILTED USING YOKE MTG.
[MORE] ORIG. FILENAME 4-55LPS & NYC-199 -5L
[LAMPCAT] T-17 SOX18
[LAMP] CLEAR 18W LOW PRESSURE SODIUM
[BALLAST] 18W LPS
[LAMPPPOSITION] HORIZONTAL

Note: Candela values converted from Type-B to Type-C

CHARACTERISTICS

IES Classification	Type I
Longitudinal Classification	Very Short
Cutoff Classification (deprecated)	Full Cutoff
Total Rated Lamp Lumens	1800
Maximum Candela	1007
Maximum Candela Angle	52.5H 12.5V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Lamp Lms)
Maximum Candela from 80 to <90 Degrees Vertical	7 (0.4% Lamp Lms)
Downward Total Efficiency	49.4%
Total Luminaire Watts	25
Ballast Factor	1.00

IES ROAD REPORT
PHOTOMETRIC FILENAME : 4000118LP.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	269.9	15.0	30.4
FM - Front-Medium (30-60)	242.8	13.5	27.3
FH - Front-High (60-80)	25.3	1.4	2.9
FVH - Front-Very High (80-90)	1.2	0.1	0.1
BL - Back-Low (0-30)	174.5	9.7	19.6
BM - Back-Medium (30-60)	154.8	8.6	17.4
BH - Back-High (60-80)	19.6	1.1	2.2
BVH - Back-Very High (80-90)	0.8	0.0	0.1
UL - Uplight-Low (90-100)	0.0	0.0	0.0
UH - Uplight-High (100-180)	0.0	0.0	0.0
Total	888.9	49.4	100.0