



UL LLC
1075 W Lambert Rd Suite B
Brea, CA 92821

Integrating Sphere Test Report

Relevant Standards
IES LM-79-2008, ANSI C82.77-10-2014, CIE 13.3-1995
CIE 15-2004, ANSI C78.377-2017, IES TM-30-2018

Prepared For
B-K Lighting INC

Daniel Carrejo
40429 Brickyard Dr.
Madera, CA 93636
United States

Catalog Number
HU-LED-TR-X115-FL-WHP-9-C-1-INC-120-PROTOTYPE(3500K)

Order Number
13244408
Test Number
13244408.20

Test Date

2020-03-25

Prepared By

Austin Duff, Technician

Approved By


Eric Gaudreau, Engineering Leader

The results contained in this report pertain only to the tested sample.
This report shall not be reproduced, except in full, without written approval of Underwriters Laboratories.
This report must not be used by the client to claim product certification, approval, or endorsement by
NVLAP, NIST, or any agency of the Federal Government.



Luminaire Description: White metal cylindrical housing and clear glass lens
Lamp: One (1) White LED with optic below
Mounting: Pendant
Ballast/Driver: One (1) ERP ESS040W-0900-42

Luminaire



Summary of Results

Radiant Flux:	10970 mW
Luminous Flux:	3580 lm
Luminaire Efficacy:	104.6 lm/W
CCT:	3616 K
CRI (Ra):	83.2
Chromaticity (x):	0.3982
Chromaticity (y):	0.3855
Chromaticity (u):	0.2332
Chromaticity (v):	0.3387
Duv:	0.0007

Test Conditions

Test Temperature:	24.9 °C
Voltage:	120.1 VAC
Current:	0.2896 A
Power:	34.23 W
Power Factor:	0.984
Frequency:	60 Hz
Current THD:	11.9 %

Testing was performed in a 2-meter integrating sphere using the 4 π geometry method.
Absorption correction was employed for this measurement.





Color Quality - Integrating Sphere

Integrating Sphere Test Conditions

Temperature	Voltage	Current	Power	Power Factor	Frequency	Current THD
24.9 °C	120.1 VAC	0.2896 A	34.23 W	0.984	60 Hz	11.9 %

Summary of Results

Total Output:	3580 Lumens	Chromaticity (x):	0.3982
Efficacy:	104.6 lm/w	Chromaticity (y):	0.3855
CCT:	3616 K	Chromaticity (u'):	0.2332
CRI (Ra):	83.2	Chromaticity (v'):	0.5080
CRI (R9):	10.9	TM-30 Rf:	84.6
Peak Wavelength:	598 nm	TM-30 Rg:	95.8
Dominant Wavelength:	581 nm	Duv:	0.0007
S/P Ratio:	1.57		



Color Rendering Index Detail

Ra (CRI)	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
83.2	81.5	90.2	95.8	81.3	81.6	86.5	85.1	63.6	10.9	76.6	79.8	67.0	83.6	97.9	75.7

