

# Photometrics

## PAR-20 Halogen

BK No.	Lamp Watts	Description	Rated Life	Center Beam Candlepower	Beam Angle	Beam Type
47	50	50PAR20/H/NSP9	2,000	6,200	9°	Narrow Spot
48	50	50PAR20/H/SP16	2,000	3,200	16°	Spot
49	50	50PAR20/H/FL30	2,000	1,400	30°	Flood

## PAR-30 Halogen

BK No.	Lamp Watts	Description	Rated Life	Center Beam Candlepower	Beam Angle	Beam Type
50	50	50PAR30L/H/NSP9	2,000	9,800	9°	Narrow Spot
51	50	50PAR30L/H/SP16	2,000	4,200	16°	Spot
52	50	50PAR30L/H/FL30	2,000	1,900	30°	Flood
53	50	50PAR30L/H/WFL40	2,000	1,250	40°	Wide Flood
54	75	75PAR30L/H/NSP9	2,000	15,500	9°	Narrow Spot
55	75	75PAR30L/H/SP16	2,000	6,700	16°	Spot
56	75	75PAR30L/H/FL30	2,000	3,400	30°	Flood
57	75	75PAR30L/H/WFL40	2,000	2,200	40°	Wide Flood

Note: If using No. 11 honeycomb baffle multiply footcandle values by .80

