






Photometrics

PAR-36 Halogen

| BK No. | Lamp Watts | Description | Rated Life | Center Beam Candlepower | Beam Angle | Beam Type |
|--------|------------|-------------|------------|-------------------------|------------|------------------|
| 25 | 18 | 4414 PAR36* | 300 | 1,500 | 50°/25° | Flood |
| 26 | 36 | 36PAR36/H | 4,000 | 25,000 | 5° | Very Narrow Spot |
| 27 | 36 | 36PAR36/H | 4,000 | 8,000 | 13° | Narrow Spot |
| 28 | 36 | 36PAR36/H | 4,000 | 900 | 30° | Flood |
| 29 | 50 | 50PAR36/H | 4,000 | 40,000 | 5° | Very Narrow Spot |
| 30 | 50 | 50PAR36/H | 4,000 | 11,000 | 8° | Narrow Spot |
| 31 | 50 | 50PAR36/H | 4,000 | 1,300 | 30° | Flood |

Note: If using No. 11 honeycomb baffle multiply footcandle values by .80

*Not a halogen lamp.







Values are center beam footcandles • Beam width to 50% of center beam footcandles

Photometrics

AR-111 Halogen

| BK No. | Lamp Watts | Description | Rated Life | Center Beam Candle power | Beam Angle | Beam Type |
|--------|------------|--------------|------------|--------------------------|------------|------------------|
| 35 | 35 | AR111/4/MNSP | 3,000 | 40,000 | 4° | Very Narrow Spot |
| 36 | 35 | AR111/8/SP | 3,000 | 14,000 | 8° | Spot |
| 37 | 35 | AR111/25/FL | 3,000 | 2,800 | 25° | Flood |
| 38 | 50 | AR111/4/MNSP | 3,000 | 50,000 | 4° | Very Narrow Spot |
| 39 | 50 | AR111/8/SP | 3,000 | 23,000 | 8° | Spot |
| 40 | 50 | AR111/25/FL | 3,000 | 4,000 | 25° | Flood |
| 41 | 75 | AR111/8/SP | 3,000 | 30,000 | 8° | Spot |
| 42 | 75 | AR111/25/FL | 3,000 | 5,300 | 25° | Flood |
| 43 | 75 | AR111/45/WFL | 3,000 | 1,700 | 45° | Wide Flood |

Note: If using No. 11 honeycomb baffle multiply footcandle values by .80



Values are center beam footcandles • Beam width to 50% of center beam footcandles