

# MINI MICRO - Wall Mount - Low Voltage - LED High-Power - Style B - 2 Fixtures - Symmetrical Optics

UPGRADED



Downloads

- Product Images (.zip)
- IES Files (.zip)
- BIM - Revit (.zip)
- Installation Instructions (.pdf)

Product Variant Examples



# MINI MICRO - Wall Mount - Low Voltage - LED High-Power - Style B - 2 Fixtures - Symmetrical Optics

## Available Logic & Configurations

**MM-** **WM-** **LOD-** **LHP-** **AL-** **BC7-** **-** **SB-F20-OSYM-** **-**  
01 02 03 04 05 06B 06C 06D 06F

**01 SERIES**

**MM** - MINI MICRO

**02 CATEGORY**

**WM** - Wall Mount

**03 DRIVER**

**LOD** - Low Voltage

**04 LIGHT SOURCE (TYPE)**

**LHP** - LED High-Power

**05 MATERIAL**

**AL** - Aluminum

**06B MOUNT**

**BC7** - Canopy BC7

**06C STYLE**

**CA** - Cap A - 45° (With Weephole)

**CB** - Cap B - 90° (With Weephole)

**CC** - Cap C - Flush Lens

**CD** - Cap D - 45°

**CE** - Cap E - 90°

**06D VERSION**

**SB-F20-OSYM** - Style B - 2 Fixtures - Symmetrical Optics

**06F SIZE**

**ST18** - Stem length: 18"

**ST24** - Stem length: 24"

**ST30** - Stem length: 30"

**ST36** - Stem length: 36"

**ST42** - Stem length: 42"

**ST48** - Stem length: 48"

**-** **-** **-** **-** **-** **-**  
07 08 10A 10B 11 12

**07 LIGHT SOURCE**

**e70** - 2700K CRI80 - 3W (139 - 167 lm)

**e71** - 3000K CRI80 - 3W (146 - 175 lm)

**e72** - 4000K CRI80 - 3W (164 - 197 lm)

**e73** - Amber - 3W

**e85** - 2700K CRI90 - 3W

**e86** - 3000K CRI90 - 3W

**e87** - 3500K CRI80 - 3W

**08 OPTIC**

**SP** - Spot (17°)

**SP2** - Spot (21°)

**NFL** - Narrow Flood (28°)

**10A LENS**

**12** - Soft Focus

**13** - Rectilinear

**10B SHIELDING**

**00** - Not included (Standard)

**11** - Honeycomb Baffle

**11 WIRING LENGTH**

**WL00** - Standard

**WL05** - 5 Ft Leads

**WL25** - 25 Ft Leads

**12 FINISH**

Standard Finishes

**BLP, BZP, WHP, SAP, BLW, BZW, WHW, VER**

Premium Finishes

**CMG, SMG, RMG, AMG, TXF, BCM, BGE, WCP, OCP, HUG, ABP, BPP, SDS,**

**WIR, CAP, CRM, AQW, NBP**

Other - RAL

**RAL**

Other - Custom Color

**CUS**

**NOTE:** Not all configurations may be compatible with one another. Please configure the product for specific 2D, Photometry, Downloads, Spec Sheet and Compatible mountings and power supplies.

# MINI MICRO - Wall Mount - Low Voltage - LED High-Power - Style B - 2 Fixtures - Symmetrical Optics

## Features



Anti-condensation vent allows moisture to exit the fixture but never enter in



Lens factory adhered to fixture cap providing hermetically sealed optical compartment



Manufactured in the USA with sustainable processes



Aim & Lock knuckle eliminates need for re-aiming & adjustments



Water-tight anti-siphon plug prevents moisture ingress from wireways



Secured with tamper-resistant, stainless steel hardware



Easily replaceable modular components reduce waste and extend fixture life



Slip fit cap & high temp. silicone 'O' ring provides reliable water-tight seal



Solid billet fixture body provides unmatched durability and heat management



360SL knuckle provides 360° horizontal rotation and vertical adjustment

**WARNING: This is a low voltage product. Please check "Mountings With A Power Supply" or "Power Supplies" to order remote transformer separately.**

## Technical

**Driver:** Low Voltage

**Light Source (Type):** LED High-Power

**Material:** Aluminum

**CCT (K):** Amber, 2700, 3500, 3000, 4000

**CRI:** 80, 90

**Input Power (W):** 3

**Delivered Lumens (lm):** 139 - 197

**Beam Angle (°):** 17, 21, 28

**Mount:** Canopy BC7

**Style:** Cap A - 45° (With Weephole), Cap B - 90° (With Weephole), Cap C - Flush Lens, Cap D - 45°, Cap E - 90°

**Version:** Style B - 2 Fixtures - Symmetrical Optics

**Size:** Stem length: 18", Stem length: 24", Stem length: 30", Stem length: 36", Stem length: 42", Stem length: 48"

**Lens:** Soft Focus, Rectilinear

**Shielding:** Not included (Standard), Honeycomb Baffle

**Wiring Length:** Standard, 5 Ft Leads, 25 Ft Leads

**Finish:** Standard Finishes, Premium Finishes, Other - RAL, Other - Custom Color

**Body:** Unibody design, with enclosed, water-proof wireway and integral heat sink, fully machined from solid billet.

**Material Detail:** Furnished in copper-free aluminum (6061-T6).

**Aiming:** 360SL provides biaxial source control with 360° horizontal rotation in addition to vertical adjustment.

**Light Source Detail:** High power LEDs modular design with electrical disconnects., Non-dimming.

**Optics:** Interchangeable optics permit changes in the field.

**Hardware:** Tamper-resistant, stainless steel hardware. Hardware is black oxide treated for additional corrosion resistance.

**Sealing:** 'O' Ring provides water-tight seal.

**Finish Detail:** StarGuard, our 15-stage chromate-free process, cleans and conversion coats aluminum components prior to application of Class 'A' TGIC polyester powder coating. It is RoHS compliant.

**Warranty:** 5-year limited warranty.

# MINI MICRO - Wall Mount - Low Voltage - LED High-Power - Style B - 2 Fixtures - Symmetrical Optics

## Finishes

### STANDARD FINISHES



[BLP]  
Satin Black



[BZP]  
Satin Bronze



[WHP]  
Satin White



[SAP]  
Satin  
Aluminum



[BLW]  
Black Wrinkle



[BZW]  
Bronze  
Wrinkle



[WHW]  
White Wrinkle



[VER]  
Verde

### PREMIUM FINISHES



[CMG]  
Cascade  
Mountain  
Granite



[SMG]  
Sierra  
Mountain  
Granite




[RMG]  
Rocky  
Mountain  
Granite




[AMG]  
Aleutian  
Mountain  
Granite



[TXF]  
Textured  
Forest



[BCM]  
Black Chrome



[BGE]  
Beige



[WCP]  
Weathered  
Copper



[OCP]  
Old Copper




[HUG]  
Hunter Green



[ABP]  
Antique Brass  
Powder



[BPP]  
Brown Patina  
Powder



[SDS]  
Sonoran  
Desert  
Sandstone




[WIR]  
Weathered  
Iron




[CAP]  
Clear  
Anodized  
Powder



[CRM]  
Cream



[AQW]  
Antique White



[NBP]  
Natural Brass  
Powder

### OTHER - RAL



[RAL]  
RAL Color

### OTHER - CUSTOM COLOR



[CUS]  
Custom Color

# MINI MICRO - Wall Mount - Low Voltage - LED High-Power - Style B - 2 Fixtures - Symmetrical Optics

## Light Source

| Light Source | Optic              | Beam Angle | CCT (K) | CRI | R9  | Input Power (W) | Delivered Lumens (Lm) | CBCP |
|--------------|--------------------|------------|---------|-----|-----|-----------------|-----------------------|------|
| e70          | SP - Spot          | 17         | 2700    | 80  | >15 | 3               | 167                   | 1347 |
| e70          | SP2 - Spot         | 21         | 2700    | 80  | >15 | 3               | 139                   | 664  |
| e70          | NFL - Narrow Flood | 28         | 2700    | 80  | >15 | 3               | 149                   | 524  |
| e71          | SP - Spot          | 17         | 3000    | 80  | >15 | 3               | 175                   | 1411 |
| e71          | SP2 - Spot         | 21         | 3000    | 80  | >15 | 3               | 146                   | 695  |
| e72          | SP - Spot          | 17         | 4000    | 80  | >15 | 3               | 197                   | 1585 |
| e72          | SP2 - Spot         | 21         | 4000    | 80  | >15 | 3               | 164                   | 781  |
| e72          | NFL - Narrow Flood | 28         | 4000    | 80  | >15 | 3               | 175                   | 616  |
| e73          | SP - Spot          | 17         | Amber   |     |     | 3               |                       |      |
| e73          | SP2 - Spot         | 21         | Amber   |     |     | 3               |                       |      |
| e73          | NFL - Narrow Flood | 28         | Amber   |     |     | 3               |                       |      |
| e85          | SP - Spot          | 17         | 2700    | 90  | >50 | 3               |                       |      |
| e85          | SP2 - Spot         | 21         | 2700    | 90  | >50 | 3               |                       |      |
| e85          | NFL - Narrow Flood | 28         | 2700    | 90  | >50 | 3               |                       |      |
| e86          | SP - Spot          | 17         | 3000    | 90  | >50 | 3               |                       |      |
| e86          | SP2 - Spot         | 21         | 3000    | 90  | >50 | 3               |                       |      |
| e86          | NFL - Narrow Flood | 28         | 3000    | 90  | >50 | 3               |                       |      |
| e87          | SP - Spot          | 17         | 3500    | 80  | >15 | 3               |                       |      |
| e87          | SP2 - Spot         | 21         | 3500    | 80  | >15 | 3               |                       |      |
| e87          | NFL - Narrow Flood | 28         | 3500    | 80  | >15 | 3               |                       |      |