

# MINI MICRO - Tree Mount - Line Voltage Via Transformer - LED High-Power - Asymmetrical Optics

UPGRADED



IP66

### Downloads

[Product Images \(.zip\)](#)

[IES Files \(.zip\)](#)

[BIM - Revit \(.zip\)](#)

[Installation Instructions \(.pdf\)](#)

### Product Variant Examples



# MINI MICRO - Tree Mount - Line Voltage Via Transformer - LED High-Power - Asymmetrical Optics

## Available Logic & Configurations

**MM-** **TM-** **LIT-** **LHP-** **AL-** **-** **-** **-**  
01 02 03 04 05 06C 06D 06F

**01 SERIES**

**MM** - MINI MICRO

**02 CATEGORY**

**TM** - Tree Mount

**03 DRIVER**

**LIT** - Line Voltage Via Transformer

**04 LIGHT SOURCE (TYPE)**

**LHP** - LED High-Power

**05 MATERIAL**

**AL** - Aluminum

**06C STYLE**

**CA** - Cap A - 45° (With Weephole)

**CB** - Cap B - 90° (With Weephole)

**CC** - Cap C - Flush Lens

**06D VERSION**

**F28-OASY** - 2 Fixtures @ 180° - Asymmetric Optics

**F32-OASY** - 3 Fixtures @ 120° - Asymmetric Optics

**F49-OASY** - 4 Fixtures @ 90° - Asymmetric Optics

**F66-OASY** - 6 Fixtures @ 60° - Asymmetric Optics

**06F SIZE**

**S16** - Strap: 16" min. to 22" max. tree diameter

**S21** - Strap: 21" min. to 27" max. tree diameter

**S26** - Strap: 26" min. to 32" max. tree diameter

**S31** - Strap: 31" min. to 38" max. tree diameter

**-** **ASY-** **NON-** **09-** **-** **WL00-** **-**  
07 08 09 10A 10B 11 12

**07 LIGHT SOURCE**

**e70** - 2700K CRI80 - 3W (151 - 151 lm)

**e71** - 3000K CRI80 - 3W (158 - 158 lm)

**e72** - 4000K CRI80 - 3W (178 - 178 lm)

**e73** - Amber - 3W

**e85** - 2700K CRI90 - 3W

**e86** - 3000K CRI90 - 3W

**e87** - 3500K CRI80 - 3W

**08 OPTIC**

**ASY** - Asymmetrical (17x31°)

**09 CONTROL**

**NON** - Non-dimming

**10A LENS**

**09** - Clear (Standard)

**10B SHIELDING**

**00** - Not included (Standard)

**11** - Honeycomb Baffle

**11 WIRING LENGTH**

**WL00** - Standard

**12 FINISH**

Standard Finishes

**BLP, BZP, WHP, SAP, BLW, BZW, WHW, VER**

Premium Finishes

**CMG, SMG, RMG, AMG, TXF, BCM, BGE, WCP, OCP, HUG, ABP, BPP, SDS,**

**WIR, CAP, CRM, AQW, NBP**

Other - RAL

**RAL**

Other - Custom Color

**CUS**

**NOTE:** Not all configurations may be compatible with one another. Please configure the product for specific 2D, Photometry, Downloads, Spec Sheet and Compatible mountings and power supplies.

# MINI MICRO - Tree Mount - Line Voltage Via Transformer - LED High-Power - Asymmetrical Optics

## Features



Anti-condensation vent allows moisture to exit the fixture but never enter in



Lens factory adhered to fixture cap providing hermetically sealed optical compartment



Manufactured in the USA with sustainable processes



Aim & Lock knuckle eliminates need for re-aiming & adjustments



Water-tight anti-siphon plug prevents moisture ingress from wireways




Secured with tamper-resistant, stainless steel hardware



Easily replaceable modular components reduce waste and extend fixture life



Slip fit cap & high temp. silicone 'O' ring provides reliable water-tight seal



Solid billet fixture body provides unmatched durability and heat management



360SL knuckle provides 360° horizontal rotation and vertical adjustment

## Technical

**Driver:** Line Voltage Via Transformer

**Light Source (Type):** LED High-Power

**Material:** Aluminum

**CCT (K):** Amber, 2700, 3500, 3000, 4000

**CRI:** 80, 90

**Input Power (W):** 3

**Delivered Lumens (lm):** 151 - 178

**Beam Angle (°):** 17x31

**Control:** Non-dimming

**Style:** Cap A - 45° (With Weephole), Cap B - 90° (With Weephole), Cap C - Flush Lens

**Version:** 2 Fixtures @ 180° - Asymmetric Optics, 3 Fixtures @ 120° - Asymmetric Optics, 4 Fixtures @ 90° - Asymmetric Optics, 6 Fixtures @ 60° - Asymmetric Optics

**Size:** Strap: 16" min. to 22" max. tree diameter, Strap: 21" min. to 27" max. tree diameter, Strap: 26" min. to 32" max. tree diameter, Strap: 31" min. to 38" max. tree diameter

**Lens:** Clear (Standard)

**Shielding:** Not included (Standard), Honeycomb Baffle

**Wiring Length:** Standard

**Finish:** Standard Finishes, Premium Finishes, Other - RAL, Other - Custom Color

**Body:** Unibody design, with enclosed, water-proof wireway and integral heat sink, fully machined from solid billet.

**Material Detail:** Tree Ring - 1/8" thick AISI 304 stainless steel. Fixture - copper-free aluminum (6061-T6).

**Aiming:** 360SL provides biaxial source control with 360° horizontal rotation in addition to vertical adjustment.

**Light Source Detail:** High power LEDs modular design with electrical disconnects., Non-dimming.

**Optics:** Interchangeable optics permit changes in the field.

**Hardware:** Tamper-resistant, stainless steel hardware. Hardware is black oxide treated for additional corrosion resistance.

**Sealing:** 'O' Ring provides water-tight seal.

**Note:** Transformer included.

**Finish Detail:** StarGuard, our 15-stage chromate-free process, cleans and conversion coats aluminum components prior to application of Class 'A' TGIC polyester powder coating. It is RoHS compliant.

**Warranty:** 5-year limited warranty.

# MINI MICRO - Tree Mount - Line Voltage Via Transformer - LED High-Power - Asymmetrical Optics

## Finishes


### STANDARD FINISHES




### PREMIUM FINISHES



### OTHER - RAL



### OTHER - CUSTOM COLOR



# MINI MICRO - Tree Mount - Line Voltage Via Transformer - LED High-Power - Asymmetrical Optics

## Light Source

Light Source	Optic	Beam Angle	CCT (K)	CRI	R9	Input Power (W)	Delivered Lumens (Lm)	CBCP
e70	ASY - Asymmetrical	17x31	2700	80	>15	3	151	613
e71	ASY - Asymmetrical	17x31	3000	80	>15	3	158	642
e72	ASY - Asymmetrical	17x31	4000	80	>15	3	178	721
e73	ASY - Asymmetrical	17x31	Amber			3		
e85	ASY - Asymmetrical	17x31	2700	90	>50	3		
e86	ASY - Asymmetrical	17x31	3000	90	>50	3		
e87	ASY - Asymmetrical	17x31	3500	80	>15	3		