MICRO NITE - Wall Mount - Line Voltage Via Transformer - LED High-Power - Style C - 2 Fixtures

(formerly Micro Nite Twin Sign Star Style C / ST-#-C-MN with PC-TRe20) & (formerly Micro Nite Twin Sign Star Style C / ST-#-C-MN with UPM)

Configure

MN-WM-LIT-LHP-AL-___-___-SC-F20-___-___-___-___-NON-___-___-WL00-___-___

01 02 03 04 05 06B 06C 06D 06F 07 08 09 10A 10B 11 12 13

MICRO NITE - Wall Mount - Line Voltage Via Transformer - LED High-Power - Aluminum - Style C - 2 Fixtures - Non-dimming - Standard

01 SERIES

MN - MICRO NITE

02 CATEGORY

WM - Wall Mount

03 DRIVER

LIT - Line Voltage Via Transformer

04 LIGHT SOURCE (TYPE)

LHP - LED High-Power

05 MATERIAL

AL - Aluminum

06B MOUNT

PC1 - Power Canopy PC1

PM1 - Universal Power Module PM1

06C STYLE

CA - Cap A - 45° (With Weephole)

CB - Cap B - 90° (With Weephole)

CC - Cap C - Flush Lens

CD - Cap D - 45°

CE - Cap E - 90°

06D VERSION

SC-F20 - Style C - 2 Fixtures

06F SIZE

ST18 - Stem length: 18"

ST24 - Stem length: 24"

ST30 - Stem length: 30"

ST36 - Stem length: 36"

ST42 - Stem length: 42"

ST48 - Stem length: 48"

07 LIGHT SOURCE

e67 - 2700K CRI80 - 7W (435 - 459 lm)

e68 - 3000K CRI80 - 7W (464 - 489 lm)

e69 - 4000K CRI80 - 7W (478 - 504 lm)

e75 - Amber - 7W

e82 - 2700K CRI90 - 7W

e83 - 3000K CRI90 - 7W

e84 - 3500K CRI80 - 7W

08 OPTIC

SP - Spot (17°)

NFL - Narrow Flood (25°)

MFL - Medium Flood (30°)

09 CONTROL

NON - Non-dimming

10A LENS

12 - Soft Focus

13 - Rectilinear

10B SHIELDING

00 - Not included (Standard)

11 - Honeycomb Baffle

11 WIRING LENGTH

WL00 - Standard

12 FINISH

Standard Finishes

BLP, **BZP**, **WHP**, **SAP**, **BLW**, **BZW**, **WHW**, **VER**

Premium Finishes

CMG, **RMG**, **AMG**, **TXF**, **BCM**, **BGE**, **WCP**, **OCP**, **HUG**, **ABP**, **BPP**, **SDS**, **WIR**, **CAP**, **CRM**, **AQW**, **NBP**

Other - RAL

RAL

Other - Custom Color

CUS

13 OPTION

CR - Camlock Mount - Round

CR-MB - Camlock Mount - Round - With Mounting Bracket

CT - Camlock Mount - Rectangular

CT-MB - Camlock Mount - Rectangular - With Mounting Bracket

SM - Surface Mount

TE - Tamper Resistant

Compatible Mounting & Power Supply Option Types

This product does not require a separate mounting or power supply. See configuration options and technical details for included mounting/power details.


Copyright © B-K Lighting, Inc. This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.


Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

MICRO NITE - Wall Mount - Line Voltage Via Transformer - LED High-Power - Style C - 2 Fixtures

(formerly Micro Nite Twin Sign Star Style C / ST-#-C-MN with PC-TRe20) & (formerly Micro Nite Twin Sign Star Style C / ST-#-C-MN with UPM)


WILDLIFE FRIENDLY







Finishes



For more detailed information and visuals regarding our finishes, visit www.bklighting.com/finishes

B-K LIGHTING AMERICAN MADE + EMPLOYEE OWNED | 40429 Brickyard Drive, Madera, CA 93636 | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Copyright © B-K Lighting, Inc. This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

MICRO NITE - Wall Mount - Line Voltage Via Transformer - LED High-Power - Style C - 2 Fixtures

(formerly Micro Nite Twin Sign Star Style C / ST-#-C-MN with PC-TRe20) & (formerly Micro Nite Twin Sign Star Style C / ST-#-C-MN with UPM)

IP66

Features



Anti-condensation vent allows moisture to exit the fixture but never enter in



Lens factory adhered to fixture cap providing hermetically sealed optical compartment



Manufactured in the USA with sustainable processes



Aim & Lock knuckle eliminates need for re-aiming & adjustments



Water-tight anti-siphon plug prevents moisture ingress from wireways



Secured with tamper-resistant, stainless steel hardware



Easily replaceable modular components reduce waste and extend fixture life



Slip fit cap & high temp. silicone 'O' ring provides reliable water-tight seal



Solid billet fixture body provides unmatched durability and heat management



360SL knuckle provides 360° horizontal rotation and vertical adjustment

Technical

Driver: Line Voltage Via Transformer

Light Source (Type): LED High-Power

Material: Aluminum

CCT (K): Amber, 2700, 3500, 3000, 4000

CRI: 80, 90

Input Power (W): 7

Delivered Lumens (lm): 435 - 504

Beam Angle (°): 17, 25, 30

Control: Non-dimming

Mount: Universal Power Module PM1, Power Canopy PC1

Style: Cap E - 90°, Cap C - Flush Lens, Cap D - 45°, Cap A - 45° (With Weephole), Cap B - 90° (With Weephole)

Version: Style C - 2 Fixtures

Input Voltage: 12V product with a connected transformer of 120V,277V

Size: Stem length: 18", Stem length: 24", Stem length: 30", Stem length: 36", Stem length: 42", Height: 42", Stem length: 48"

Lens: Soft Focus, Rectilinear

Shielding: Not included (Standard), Honeycomb Baffle

Wiring Length: Standard

Finish: Standard Finishes, Premium Finishes, Other - RAL, Other - Custom Color

Option: Camlock Mount - Round, Camlock Mount - Round - With Mounting Bracket, Camlock Mount - Rectangular, Camlock Mount - Rectangular - With Mounting Bracket, Surface Mount, Tamper Resistant

IP Rating: IP66 rated

Installation Fixture: Safety Cable included for stem lengths 30" and above.

EPA (ft2): 0.25 - 0.51

Source to Lens Distance (in): 0.77

Body: Unibody design, with enclosed, water-proof wireway and integral heat sink, fully machined from solid billet.

Material Detail: Furnished in copper-free aluminum (6061-T6).

Aiming: 360SL provides biaxial source control with 360° horizontal rotation in addition to vertical adjustment.

Light Source Detail: High power LEDs modular design with electrical disconnects.

Optics: Interchangeable optics permit changes in the field.

Hardware: Tamper-resistant, stainless steel hardware. Hardware is black oxide treated for additional corrosion resistance.

Sealing: High temperature silicone 'O' Ring in fixture knuckle provides water-tight seal at joint.

Finish Detail: StarGuard, our 15-stage chromate-free process, cleans and conversion coats aluminum components prior to application of Class 'A' TGIC polyester powder coating. It is RoHS compliant.

Warranty: 5-year limited warranty.

Certification: Made in USA, UL Listed, Turtle Friendly, Suitable for Wet Locations

Power Supply / Driver / Transformer: Transformer included.

Copyright © B-K Lighting, Inc. This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Updated 11/20/2026

MICRO NITE - Wall Mount - Line Voltage Via Transformer - LED High-Power - Style C - 2 Fixtures

(formerly Micro Nite Twin Sign Star Style C / ST-#-C-MN with PC-TRe20) & (formerly Micro Nite Twin Sign Star Style C / ST-#-C-MN with UPM)

Light Source

Configure your product to display exact performance values

Light Source	Optic	Beam Angle	CCT (K)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP
-	-	-	-	-	-	-	-

Without selecting your configuration

Light Source	Optic	Beam Angle	CCT (K)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP
e67	SP - Spot	17°	2700	80	7	459	3632
e67	NFL - Narrow Flood	25°	2700	80	7	435	1708
e67	MFL - Medium Flood	30°	2700	80	7	438	1337
e68	SP - Spot	17°	3000	80	7	489	3871
e68	NFL - Narrow Flood	25°	3000	80	7	464	1821
e68	MFL - Medium Flood	30°	3000	80	7	467	1425
e69	SP - Spot	17°	4000	80	7	504	3991
e69	NFL - Narrow Flood	25°	4000	80	7	478	1877
e69	MFL - Medium Flood	30°	4000	80	7	481	1469
e75	SP - Spot	17°			7		
e75	NFL - Narrow Flood	25°			7		
e75	MFL - Medium Flood	30°	Amber		7		
e82	SP - Spot	17°	2700	90	7		
e82	NFL - Narrow Flood	25°	2700	90	7		
e82	MFL - Medium Flood	30°	2700	90	7		
e83	SP - Spot	17°	3000	90	7		
e83	NFL - Narrow Flood	25°	3000	90	7		
e83	MFL - Medium Flood	30°	3000	90	7		
e84	SP - Spot	17°	3500	80	7		
e84	NFL - Narrow Flood	25°	3500	80	7		
e84	MFL - Medium Flood	30°	3500	80	7		

Copyright © B-K Lighting, Inc. This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com