

NITE STAR - Bollard - Line Voltage Via Transformer - LED High-Power - Style C - Single - Wildlife Friendly

WILDLIFE FRIENDLY



IP66

Downloads

- Product Images (.zip)
- Technical Drawing (.zip)
- BIM - Revit
- Installation Instructions (.pdf)

Product Variant Examples



NITE STAR - Bollard - Line Voltage Via Transformer - LED High-Power - Style C - Single - Wildlife Friendly

Available Logic & Configurations

NS- 01	BO- 02	LIT- 03	LHP- 04	AL- 05	RO- 06A	PP1-J18- 06B	- 06C	SC-F10- 06D	- 06F
01 SERIES NS - NITE STAR 02 CATEGORY BO - Bollard 03 DRIVER LIT - Line Voltage Via Transformer 04 LIGHT SOURCE (TYPE) LHP - LED High-Power				05 MATERIAL AL - Aluminum 06A SHAPE RO - Round 06B MOUNT PP1-J18 - Power Pipe PP1 - 18" Junction Box 06C STYLE CA - Cap A - 45° (With Weephole) CB - Cap B - 90° (With Weephole) CC - Cap C - Flush Lens CD - Cap D - 45° CE - Cap E - 90° CF - Cap F - Extended Flush Lens 06D VERSION SC-F10 - Style C - Single 06F SIZE H24 - Height: 24" H30 - Height: 30" H36 - Height: 36" H42 - Height: 42" H48 - Height: 48"					
e74- 07	- 08	NON- 09	12- 10A	- 10B	WL00- 11	- 12			
07 LIGHT SOURCE e74 - Amber - 7W (260 - 299 lm) 08 OPTIC NSP - Narrow Spot (13°) SP - Spot (16°) SP2 - Spot (23°) MFL - Medium Flood (31°)				09 CONTROL NON - Non-dimming 10A LENS 12 - Soft Focus 10B SHIELDING 00 - Not included (Standard) 11 - Honeycomb Baffle 11 WIRING LENGTH WL00 - Standard 12 FINISH Standard Finishes BLP, BZP, WHP, SAP, BLW, BZW, WHW, VER Premium Finishes CMG, SMG, RMG, AMG, TXF, BCM, BGE, WCP, OCP, HUG, ABP, BPP, SDS, WIR, CAP, CRM, AQW, NBP Other - RAL RAL Other - Custom Color CUS					

NOTE: Not all configurations may be compatible with one another. Please configure the product for specific 2D, Photometry, Downloads, Spec Sheet and Compatible mountings and power supplies.

NITE STAR - Bollard - Line Voltage Via Transformer - LED High-Power - Style C - Single - Wildlife Friendly

Features



Anti-condensation vent allows moisture to exit the fixture but never enter in



Lens factory adhered to fixture cap providing hermetically sealed optical compartment



Manufactured in the USA with sustainable processes



Aim & Lock knuckle eliminates need for re-aiming & adjustments



Water-tight anti-siphon plug prevents moisture ingress from wireways



Secured with tamper-resistant, stainless steel hardware



Easily replaceable modular components reduce waste and extend fixture life



Slip fit cap & high temp. silicone 'O' ring provides reliable water-tight seal



Solid billet fixture body provides unmatched durability and heat management



360SL knuckle provides 360° horizontal rotation and vertical adjustment

WARNING: This is a low voltage product. Please check "Mountings With A Power Supply" or "Power Supplies" to order remote transformer separately.

Technical

Driver: Line Voltage Via Transformer, Low Voltage

Light Source (Type): LED High-Power

Material: Aluminum

CCT (K): Amber

Input Power (W): 7

Delivered Lumens (lm): 260 - 299

Beam Angle (°): 13, 16, 23, 31

Control: Non-dimming

Shape: Round

Mount: Anchor Base, Power Pipe PP1 - 18" Junction Box

Style: Cap A - 45° (With Weephole), Cap B - 90° (With Weephole), Cap C - Flush Lens, Cap D - 45°, Cap E - 90°, Cap F - Extended Flush Lens

Version: Style C - Single

Size: Height: 24", Height: 30", Height: 36", Height: 42", Height: 48", Height: 54", Height: 60", Height: 66", Height: 72"

Lens: Soft Focus

Shielding: Not included (Standard), Honeycomb Baffle

Wiring Length: Standard

Finish: Standard Finishes, Premium Finishes, Other - RAL, Other - Custom Color

Body: Unibody design with enclosed, water-proof wireway, integral heat sink, fully machined from solid billet, anti-condensation and corrosion vent equalizes fixture pressure and eliminates potential for damage to internal components.

Material Detail: Furnished in copper-free aluminum (6061-T6).

Aiming: Knuckle enables 180° vertical adjustment. 'O' Ring helps maintain fixture position. Design withstands 73 lbs. static load prior to movement for optical alignment. Mounts with a 1/2" pipe thread.

Light Source Detail: High power LEDs modular design with electrical disconnects.

Optics: Interchangeable optics permit changes in the field.

Hardware: Tamper-resistant, stainless steel hardware. Hardware is black oxide treated for additional corrosion resistance.

Sealing: 'O' Ring provides water-tight seal., Anti-condensation and corrosion vent equalizes fixture pressure and eliminates potential for damage to internal components.

Note: Stability Flange included., Transformer included., Adjust-e-Lume, an LED board feature, allows for dynamic lumen response at the individual fixture. Indexed (100% to 25% nom.) lumen output. Maintains output at desired level or may be changed (A9 to A1). Standard preset from the factory is A9 (100%).

Finish Detail: StarGuard, our 15-stage chromate-free process, cleans and conversion coats aluminum components prior to application of Class 'A' TGIC polyester powder coating. It is RoHS compliant.

Warranty: 5-year limited warranty.

NITE STAR - Bollard - Line Voltage Via Transformer - LED High-Power - Style C - Single - Wildlife Friendly

Finishes

STANDARD FINISHES




PREMIUM FINISHES



OTHER - RAL



OTHER - CUSTOM COLOR



NITE STAR - Bollard - Line Voltage Via Transformer - LED High-Power - Style C - Single - Wildlife Friendly

Light Source

Light Source	Optic	Beam Angle	CCT (K)	CRI	R9	Input Power (W)	Delivered Lumens (Lm)	CBCP
e74	NSP - Narrow Spot	13	Amber			7	299	3927
e74	SP - Spot	16	Amber			7	291	2978
e74	SP2 - Spot	23	Amber			7	260	1131
e74	MFL - Medium Flood	31	Amber			7	262	741