

# YUKON - Bollard - Line Voltage - LED High-Power - Indirect

UPGRADED



IP66

### Downloads

- Product Images (.zip)
- Technical Drawing (.zip)
- IES Files (.zip)
- BIM - Revit (.zip)
- Installation Instructions (.pdf)

### Product Variant Examples



# YUKON - Bollard - Line Voltage - LED High-Power - Indirect

## Available Logic & Configurations

**YK-** 01   **BO-** 02   **LID-** 03   **LHP-** 04   **AL-** 05   **AB-** 06B   **---** 06C   **IN-** 06D   **---** 06E   **---** 06F

- 01 SERIES**  
YK - YUKON
- 02 CATEGORY**  
BO - Bollard
- 03 DRIVER**  
LID - Line Voltage
- 04 LIGHT SOURCE (TYPE)**  
LHP - LED High-Power

- 05 MATERIAL**  
AL - Aluminum
- 06B MOUNT**  
AB - Anchor Base
- 06C STYLE**  
FLD-BCU - Faceplate: Louvered - Backplate: Curved  
FSD-BCU - Faceplate: Standard - Backplate: Curved  
FSD-BST - Faceplate: Standard - Backplate: Stepped
- 06D VERSION**  
IN - Indirect
- 06E INPUT VOLTAGE**  
120 - 120V  
277 - 277V
- 06F SIZE**  
H18 - Height: 18"  
H24 - Height: 24"  
H30 - Height: 30"  
H30-REC - Height 30" - With Receptacle  
H36 - Height: 36"  
H36-REC - Height 36" - With Receptacle  
H42 - Height: 42"  
H42-REC - Height 42" - With Receptacle

**---** 07   **---** 09   **WL00-** 11   **---** 12   **---** 13

- 07 LIGHT SOURCE**  
I2780 - 2700K CRI80 - 12W (220 - 443 lm)  
I2790 - 2700K CRI90 - 12W (184 - 370 lm)  
I3080 - 3000K CRI80 - 12W (225 - 453 lm)  
I3090 - 3000K CRI90 - 12W (188 - 378 lm)  
I3580 - 3500K CRI80 - 12W (232 - 467 lm)  
I3590 - 3500K CRI90 - 12W (194 - 390 lm)  
I4080 - 4000K CRI80 - 12W (239 - 481 lm)  
I4090 - 4000K CRI90 - 12W (200 - 402 lm)

- 09 CONTROL**  
ELV - ELV Dimming (For use with Electronic Low Voltage Dimmer. 120V only.)  
INC - INC Dimming (For use with Incandescent Dimmer. 120V only.)  
010 - 0-10V (120V,277V)
- 11 WIRING LENGTH**  
WL00 - Standard
- 12 FINISH**  
Standard Finishes  
BLP, BZP, WHP, SAP, BLW, BZW, WHW, VER  
Premium Finishes  
CMG, SMG, RMG, AMG, TXF, BCM, BGE, WCP, OCP, HUG, ABP, BPP, SDS,  
WIR, CAP, CRM, AQW, NBP  
Other - RAL  
RAL  
Other - Custom Color  
CUS
- 13 OPTION**  
BF - Black wrinkle finish on backplate for glare reduction  
RE1-YKB - (2) Receptacles with 20A GFCI  
RE2-YKB - (2) Receptacles with 20A GFCI and USB Type A/C Charging Ports  
RE1-RE2-YKB - (1) Receptacle with 20A GFCI / (1) Receptacle with 20A GFCI and USB Type A/C Charging Ports

**NOTE:** Not all configurations may be compatible with one another. Please configure the product for specific 2D, Photometry, Downloads, Spec Sheet and Compatible mountings and power supplies.

# YUKON - Bollard - Line Voltage - LED High-Power - Indirect

## Features



Secured with hidden tamper-resistant stainless steel hardware



Internal optics with adjustable aim



Manufactured in the USA with sustainable processes



Easily replaceable modular components reduce waste and extend fixture life

## Technical

**Driver:** Line Voltage

**Light Source (Type):** LED High-Power

**Material:** Aluminum

**CCT (K):** 2700, 3500, 3000, 4000

**CRI:** 80, 90

**Input Power (W):** 12

**Delivered Lumens (lm):** 184 - 481

**Control:** 0-10V (120V, 277V), ELV Dimming (For use with Electronic Low Voltage Dimmer. 120V only.), INC Dimming (For use with Incandescent Dimmer. 120V only.)

**Mount:** Anchor Base

**Style:** Faceplate: Standard - Backplate: Stepped, Faceplate: Standard - Backplate: Curved, Faceplate: Louvered - Backplate: Curved

**Version:** Indirect

**Input Voltage:** 120V, 277V

**Size:** Height: 18", Height: 24", Height: 30", Height 30" - With Receptacle, Height: 36", Height 36" - With Receptacle, Height: 42", Height 42" - With Receptacle

**Wiring Length:** Standard

**Finish:** Standard Finishes, Premium Finishes, Other - RAL, Other - Custom Color

**Option:** Black wrinkle finish on backplate for glare reduction, (1) Receptacle with 20A GFCI / (1) Receptacle with 20A GFCI and USB Type A/C Charging Ports, (2) Receptacles with 20A GFCI, (2) Receptacles with 20A GFCI and USB Type A/C Charging Ports

**Material Detail:** Furnished in copper-free aluminum (6061-T6).

**Aiming:** Adjustable heat sink allows for distribution adjustment in the field.

**Light Source Detail:** High power LEDs modular design with electrical disconnects.

**Hardware:** Tamper-resistant, stainless steel hardware.

**Sealing:** Anti-condensation and corrosion vent equalizes fixture pressure and eliminates potential for damage to internal components., Weather tight, gasketed in-use receptacle cover.

**Note:** Receptacle option only available in 30" height and above.

**Finish Detail:** StarGuard, our 15-stage chromate-free process, cleans and conversion coats aluminum components prior to application of Class 'A' TGIC polyester powder coating. It is RoHS compliant.

**Warranty:** 5-year limited warranty.

# YUKON - Bollard - Line Voltage - LED High-Power - Indirect

## Finishes

### STANDARD FINISHES



[BLP] Satin Black



[BZP] Satin Bronze



[WHP] Satin White



[SAP] Satin Aluminum



[BLW] Black Wrinkle



[BZW] Bronze Wrinkle



[WHW] White Wrinkle



[VER] Verde

### PREMIUM FINISHES



[CMG] Cascade Mountain Granite



[SMG] Sierra Mountain Granite



[RMG] Rocky Mountain Granite




[AMG] Aleutian Mountain Granite



[TXF] Textured Forest



[BCM] Black Chrome



[BGE] Beige



[WCP] Weathered Copper



[OCP] Old Copper



[HUG] Hunter Green



[ABP] Antique Brass Powder



[BPP] Brown Patina Powder




[SDS] Sonoran Desert Sandstone



[WIR] Weathered Iron



[CAP] Clear Anodized Powder



[CRM] Cream



[AQW] Antique White



[NBP] Natural Brass Powder

### OTHER - RAL



[RAL] RAL Color

### OTHER - CUSTOM COLOR



[CUS] Custom Color

# YUKON - Bollard - Line Voltage - LED High-Power - Indirect

## Light Source

Light Source	Optic	Beam Angle	CCT (K)	CRI	R9	Input Power (W)	Delivered Lumens (Lm)	CBCP
I2780	-	60	2700	80	>15	12	381	
I2780	-	60	2700	80	>15	12	362	
I2780	-	60	2700	80	>15	12	252	
I2780	-	60	2700	80	>15	12	320	
I2790	-	60	2700	90	>50	12	318	
I2790	-	60	2700	90	>50	12	302	
I2790	-	60	2700	90	>50	12	211	
I2790	-	60	2700	90	>50	12	267	
I3080	-	60	3000	80	>15	12	390	
I3080	-	60	3000	80	>15	12	370	
I3080	-	60	3000	80	>15	12	258	
I3080	-	60	3000	80	>15	12	328	
I3090	-	60	3000	90	>50	12	326	
I3090	-	60	3000	90	>50	12	309	
I3090	-	60	3000	90	>50	12	216	
I3090	-	60	3000	90	>50	12	274	
I3580	-	60	3500	80	>15	12	402	
I3580	-	60	3500	80	>15	12	382	
I3580	-	60	3500	80	>15	12	266	
I3580	-	60	3500	80	>15	12	338	
I3590	-	60	3500	90	>50	12	336	
I3590	-	60	3500	90	>50	12	319	
I3590	-	60	3500	90	>50	12	222	
I3590	-	60	3500	90	>50	12	282	
I4080	-	60	4000	80	>15	12	414	
I4080	-	60	4000	80	>15	12	393	
I4080	-	60	4000	80	>15	12	274	
I4080	-	60	4000	80	>15	12	348	
I4090	-	60	4000	90	>50	12	346	
I4090	-	60	4000	90	>50	12	328	
I4090	-	60	4000	90	>50	12	229	
I4090	-	60	4000	90	>50	12	291	
I2780	-	60	2700	80	>15	12	443	
I2790	-	60	2700	90	>50	12	370	
I3080	-	60	3000	80	>15	12	453	
I3090	-	60	3000	90	>50	12	378	
I3580	-	60	3500	80	>15	12	467	
I3590	-	60	3500	90	>50	12	390	
I4080	-	60	4000	80	>15	12	481	
I4090	-	60	4000	90	>50	12	402	
I2780	-	60	2700	80	>15	12	220	
I2790	-	60	2700	90	>50	12	184	
I3080	-	60	3000	80	>15	12	225	
I3090	-	60	3000	90	>50	12	188	
I3580	-	60	3500	80	>15	12	232	
I3590	-	60	3500	90	>50	12	194	
I4080	-	60	4000	80	>15	12	239	
I4090	-	60	4000	90	>50	12	200	